

贴片电容器产品规格表

SERIES	APPLICATION	OPERATING TEMPERATURE RANGE (°C)	VOLTAGE RANGE	CAPACITANCE RANGE (mF)	CAPACITANCE TOLERANCE	LEAKAGE CURRENT (mA MAX.)	CASE SIZE D×L Life
Aluminum Electrolytic Capacitors	VS	Wide Temperature Range	-40~+85	4V~50V	0.1~10000	±20%	0.01CV or 3A after 2min. 4*5.4~18*21.5 2000hrs
	VT	Miniature Sized, Wide T	-40~+105	4V~100V	0.1~8200	±20%	0.01CV or 3A after 2min. 4*5.4~18*21.5 1000hrs
	LHB	Long Life	-55~+105	4V~100V	0.1~8200	±20%	0.01CV or 3A after 2min. 4*5.4~18*21.5 2000hrs
	LHL	Long Life	-55~+105	6.3V~100V	1~1500	±20%	0.01CV or 3A after 2min. 4*5.4~18*21.5 3000hrs
	LHM	Long Life	-40~+105	6.3V~100V	1~7500	±20%	0.01CV or 3A after 2min. 4*5.4~18*21.5 3000~5000hrs
	VD	Low Impedance	-55~+105	6.3V~100V	1~8200	±20%	0.01CV or 3A after 2min. 4*5.4~18*21.5 2000~8000hrs
	LHZ	Low Impedance	-55~+105	6.3V~35V	4.7~1500	±20%	0.01CV or 3A after 2min. 4*5.8~10*10.5 2000hrs
	LHS	Low Impedance	-55~+105	6.3V~35V	22~1500	±20%	0.01CV or 3A after 2min. 5*5.8~10*10.5 2000hrs
	LHD	Low Impedance	-55~+105	6.3 V ~100V	10~2200	±20%	0.01CV or 3A after 2min. 4*5.8~10*10.5 2000~5000hrs
	LHN	Bipolar	-40~+85	6.3 V ~50V	0.1~220	±20%	0.05CVor10A after 2min. 4*5.4~8*10.5 2000hrs
	LSS	Low Leakage	-40~+85	6.3 V ~50V	1~150	±20%	0.002CVor0.5uA 4*5.4~6.3*7.7 2000hrs
	LHU	High Temperature	-40~+125	10 V ~250V	22~4700	±20%	0.01CV or 3A after 2min. 6.3*5.4~18*16.5 1000~2000hrs
	LHI	Miniature Sized, Wide	-40~+85	4V~100V	0.47~220	±20%	0.01CV or 3A after 2min. 4*4.5~6.3*4.5 2000hrs
	LHA	Low Impedance	-40~+125	10 V ~100V	100~3300	±20%	0.01CV or 3A after 2min. 8*6.2~18*21.5 1000~2000hrs
	JVD	HighVoltageHighReliability	-40~+105	160 V ~450V	1~100	±20%	0.04 CV+100uA after 2min. 6.3*7.7~18*16.5 2000~5000hrs
	LHT	Ordinaryminiatureproducts	-40~+105	6.3V~63V	10~2200	±20%	0.01CV or 3A after 2min. 5*5.8~10*10.5 2000hrs
	LHW	Low Impedance	-55~+125	10 V ~100V	10~1000	±20%	0.01CV or 3A after 2min. 6.3*7.7~12.5*16.5 2000~3000hrs
	LHV	Low Impedance	-40~+125	10 V ~100V	22~4700	±20%	0.01CV or 3A after 2min. 8*10.5~18*21.5 3000~5000hrs
	LHF	LowImpedanceLong Life	-55~+105	6.3V~50V	100~1500	±20%	0.01CV or 3A after 2min. 6.3*7.7~10*10.5 5000hrs
	LHH	LowImpedanceLong Life	-55~+105	6.3V~50V	22~680	±20%	0.01CV or 3A after 2min. 6.3*7.7~10*10.5 7000~10000hrs
LHO	Miniature Sized, Wide	-40~+105	4V~50V	1~220	±20%	0.01CV or 3A after 2min. 4*3.95~6.3*3.95 1000hrs	
LHC	Low Impedance	-55~+105	6.3V~35V	1~220	±20%	0.01CV or 3A after 2min. 4*5.4~6.3*7.7 2000hrs	
LHJ	HighVoltageHighReliability	-40~+105	160 V ~450V	1~100	±20%	0.04 CV+100uA after 2min. 6.3*7.7~18*16.5 2000hrs	
LHK	HighVoltageHighReliability	-40~+105	160 V ~450V	1.8~33	±20%	0.04 CV+100uA after 2min. 8*10.5~10*12.5 8000~10000hrs	